


JC10 Rec'd PCT/PTO 26 FEB 2002

FORM PTO-1390 (REV. 9-2001)		U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE		ATTORNEY'S DOCKET NUMBER 1712934	
TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371				U.S. APPLICATION NO. (known, 2001 PCT/FR 02413) 10/069507	
				None yet assigned	
INTERNATIONAL APPLICATION NO. PCT/FR00/02413		INTERNATIONAL FILING DATE August 31, 2000		PRIORITY DATE CLAIMED August 31, 1999	
TITLE OF INVENTION Device for Regulating Flow in a Duct Portion or an Intake Passage and Manifold Comprising Same					
APPLICANT(S) FOR DO/EO/US MOREAU, Fabien, and KOMURIAN, Richard					
Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:					
<p>1. <input checked="" type="checkbox"/> This is a FIRST submission of items concerning a filing under 35 U.S.C. 371.</p> <p>2. <input type="checkbox"/> This is a SECOND or SUBSEQUENT submission of items concerning a filing under 35 U.S.C. 371.</p> <p>3. <input type="checkbox"/> This is an express request to begin national examination procedures (35 U.S.C. 371(f)). The submission must include items (5), (6), (9) and (21) indicated below.</p> <p>4. <input checked="" type="checkbox"/> The US has been elected by the expiration of 19 months from the priority date (Article 31).</p> <p>5. <input checked="" type="checkbox"/> A copy of the International Application as filed (35 U.S.C. 371(c)(2))</p> <p style="margin-left: 20px;">a. <input checked="" type="checkbox"/> is attached hereto (required only if not communicated by the International Bureau).</p> <p style="margin-left: 20px;">b. <input type="checkbox"/> has been communicated by the International Bureau.</p> <p style="margin-left: 20px;">c. <input type="checkbox"/> is not required, as the application was filed in the United States Receiving Office (RO/US).</p> <p>6. <input type="checkbox"/> An English language translation of the International Application as filed (35 U.S.C. 371(c)(2)).</p> <p style="margin-left: 20px;">a. <input type="checkbox"/> is attached hereto.</p> <p style="margin-left: 20px;">b. <input type="checkbox"/> has been previously submitted under 35 U.S.C. 154(d)(4).</p> <p>7. <input type="checkbox"/> Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3))</p> <p style="margin-left: 20px;">a. <input type="checkbox"/> are attached hereto (required only if not communicated by the International Bureau).</p> <p style="margin-left: 20px;">b. <input type="checkbox"/> have been communicated by the International Bureau.</p> <p style="margin-left: 20px;">c. <input type="checkbox"/> have not been made; however, the time limit for making such amendments has NOT expired.</p> <p style="margin-left: 20px;">d. <input type="checkbox"/> have not been made and will not be made.</p> <p>8. <input type="checkbox"/> An English language translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371 (c)(3)).</p> <p>9. <input type="checkbox"/> An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).</p> <p>10. <input type="checkbox"/> An English language translation of the annexes of the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).</p> <p>Items 11 to 20 below concern document(s) or information included:</p> <p>11. <input type="checkbox"/> An Information Disclosure Statement under 37 CFR 1.97 and 1.98.</p> <p>12. <input type="checkbox"/> An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.</p> <p>13. <input type="checkbox"/> A FIRST preliminary amendment.</p> <p>14. <input type="checkbox"/> A SECOND or SUBSEQUENT preliminary amendment.</p> <p>15. <input type="checkbox"/> A substitute specification.</p> <p>16. <input type="checkbox"/> A change of power of attorney and/or address letter.</p> <p>17. <input type="checkbox"/> A computer-readable form of the sequence listing in accordance with PCT Rule 13ter.2 and 35 U.S.C. 1.821 - 1.825.</p> <p>18. <input type="checkbox"/> A second copy of the published international application under 35 U.S.C. 154(d)(4).</p> <p>19. <input type="checkbox"/> A second copy of the English language translation of the international application under 35 U.S.C. 154(d)(4).</p> <p>20. <input checked="" type="checkbox"/> Other items or information: International Search Report, 1st Page Published PCT Application International Preliminary Examination Report, with Annex (Claims as Amended under PCT Article 34) Application Data Sheet Express Mail Certificate Label No. EK 288 571 650 US</p>					

page 1 of 2

1327192
1712934

JC19 Rec'd PCT/PTO 26 FEB 2002

U.S. APPLICATION NO. 10/069507 INTERNATIONAL APPLICATION NO. PCT/FR 00/02413		ATTORNEY'S DOCKET NUMBER 1712934																										
21. <input checked="" type="checkbox"/> The following fees are submitted: BASIC NATIONAL FEE (37 CFR 1.492 (a) (1) - (5)): Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO \$1040.00 International preliminary examination fee (37 CFR 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO \$890.00 International preliminary examination fee (37 CFR 1.482) not paid to USPTO but international search fee (37 CFR 1.445(a)(2)) paid to USPTO \$740.00 International preliminary examination fee (37 CFR 1.482) paid to USPTO but all claims did not satisfy provisions of PCT Article 33(1)-(4) \$710.00 International preliminary examination fee (37 CFR 1.482) paid to USPTO and all claims satisfied provisions of PCT Article 33(1)-(4) \$100.00 ENTER APPROPRIATE BASIC FEE AMOUNT =		CALCULATIONS PTO USE ONLY																										
Surcharge of \$130.00 for furnishing the oath or declaration later than <input type="checkbox"/> 20 <input checked="" type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(e)).		\$	890																									
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 20%;">CLAIMS</th> <th style="width: 20%;">NUMBER FILED</th> <th style="width: 20%;">NUMBER EXTRA</th> <th style="width: 20%;">RATE</th> <th style="width: 20%;">\$</th> </tr> </thead> <tbody> <tr> <td>Total claims</td> <td>17 - 20 =</td> <td>0</td> <td>x \$18.00</td> <td>\$</td> </tr> <tr> <td>Independent claims</td> <td>1 - 3 =</td> <td>0</td> <td>x \$84.00</td> <td>\$</td> </tr> <tr> <td colspan="4">MULTIPLE DEPENDENT CLAIM(S) (if applicable)</td> <td>+ \$280.00</td> </tr> <tr> <td colspan="4">TOTAL OF ABOVE CALCULATIONS =</td> <td>\$</td> </tr> </tbody> </table>		CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE	\$	Total claims	17 - 20 =	0	x \$18.00	\$	Independent claims	1 - 3 =	0	x \$84.00	\$	MULTIPLE DEPENDENT CLAIM(S) (if applicable)				+ \$280.00	TOTAL OF ABOVE CALCULATIONS =				\$	\$	130
CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE	\$																								
Total claims	17 - 20 =	0	x \$18.00	\$																								
Independent claims	1 - 3 =	0	x \$84.00	\$																								
MULTIPLE DEPENDENT CLAIM(S) (if applicable)				+ \$280.00																								
TOTAL OF ABOVE CALCULATIONS =				\$																								
<input type="checkbox"/> Applicant claims small entity status. See 37 CFR 1.27. The fees indicated above are reduced by 1/2.		\$																										
SUBTOTAL =		\$	1020																									
Processing fee of \$130.00 for furnishing the English translation later than <input type="checkbox"/> 20 <input checked="" type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(f)).		\$	130																									
TOTAL NATIONAL FEE =		\$	1,150																									
Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). \$40.00 per property +		\$																										
TOTAL FEES ENCLOSED =		\$	1,150																									
		Amount to be refunded:	\$																									
		charged:	\$																									
a. <input checked="" type="checkbox"/> A check in the amount of \$ <u>1,150</u> to cover the above fees is enclosed. b. <input type="checkbox"/> Please charge my Deposit Account No. _____ in the amount of \$ _____ to cover the above fees. A duplicate copy of this sheet is enclosed. c. <input checked="" type="checkbox"/> The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. <u>50-0305</u> . A duplicate copy of this sheet is enclosed. d. <input type="checkbox"/> Fees are to be charged to a credit card. WARNING: Information on this form may become public. Credit card information should not be included on this form. Provide credit card information and authorization on PTO-2038.																												
NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137 (a) or (b)) must be filed and granted to restore the application to pending status.																												
SEND ALL CORRESPONDENCE TO: Robert J. Schneider Chapman and Cutler 111 West Monroe Street Chicago, Illinois 60603 (312) 845-3919																												
		SIGNATURE  Jane S. Berman NAME 43,494 REGISTRATION NUMBER																										

107069507 0231402

JC19 Rec'd PCT/PTO 26 FEB 2002

EXPRESS MAIL CERTIFICATE

Express Mail Label Number: EK 288 571 650 US

Date of Deposit: February 26, 2002

I hereby certify that the attached documents are being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR § 1.10 on the date indicated above and is addressed Commissioner for Patents, Box PCT, Washington, D.C. 20231.

Brenda A. Walton

(Typed or printed name of person
mailing paper or fee)

Brenda A. Walton

(Signature of person mailing paper
or fee)

10 Rec'd 10069507 .081402 #5
14 AUG 2002

ATTORNEY DOCKET NO. 1712934

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

IN RE PATENT APPLICATION OF:

MOREAU, ET AL.

U.S. APPLICATION SERIAL NO.
10/069,507

INTERNATIONAL APPLICATION NO.
PCT/FR00/02413

U.S. FILING DATE:
FEBRUARY 26, 2002

FOR: DEVICE FOR REGULATING FLOW IN A
DUCT PORTION OR AN INTAKE
PASSAGE AND MANIFOLD
COMPRISING SAME

EXAMINER: UNKNOWN
GROUP ART UNIT: UNKNOWN

Submitted with Response to Notice of Missing Requirements issued May 15, 2002

ATTACHED: ENGLISH LANGUAGE TRANSLATION

**OF SPECIFICATION OF INTERNATIONAL APPLICATION NO. PCT/FR00/02413,
AS FILED.**

Attorneys for Applicant:
Robert J. Schneider
CHAPMAN AND CUTLER
111 W. Monroe Street
Chicago, IL 60603-4080
(312) 845-3919

Patent Application Serial No

30065507/069507

10 REG 10000 14 AUG 2002

DEVICE FOR REGULATING FLOW IN A DUCT PORTION OR AN
INTAKE PASSAGE AND MANIFOLD COMPRISING SAME

1006957/069587 #5

10 Rev 6 7 10 40 14 AUG 2002

DESCRIPTION

The present invention relates to the field concerning the control of flow in fluids, in particular gases, and more particularly in the framework of air intake for combustion engines, for example in connection with intake manifolds, but also and more generally to devices for regulating flow in an intake passage by means of an element placed within said intake passage and drivable by means of a control shaft.

More precisely, the object of the present invention is a device for regulating flow in a duct portion or an intake passage, a manifold comprising said device et a method to produce such manifold.

At present the interconnection of a device for

regulating or controlling flow in an intake passage of a duct portion or similar is generally carried out with one or more particular operations both by mounting a transversal insert supporting the regulation element in said duct portion after cutting a suitable opening within said portion, and by placing an intermediate duct segment equipped with said regulation element between two spaced parts of said duct portion.

However, these known methods require both the production of complex inserts, comprising beyond the regulation element also a wall portion or pre-mounted supporting structures whose inner and sealed assembly with the wall portions housing the duct portion or similar is quite difficult to be carried out, and the supply and installation of additional adjustment or integration intermediate or intercalary parts, whose only aim is the mounting of said regulation element and which are no structural part belonging to said duct portion or similar.

Furthermore, these known methods generally give rise to embrittlement areas on the assembly planes or lines of the different structural parts (attached pieces) and require technical operations or additional pieces for fabricating the duct portion or

similar (with no regulation device).

Moreover, the assemblies obtained with these known methods have bulky overall dimensions because of their structure and generally of a displaced and protruding control.

The present invention aims in particular at obviating at least some of these disadvantages.

To this purpose its object is a device for regulating the flow of a fluid, in particular a gas, in at least a duct portion, an intake passage or similar by means of a valve or of a similar revolving obstruction element, supported by a control shaft, characterized in that each assembly valve/control shaft is integrated into the structure of the duct portion concerned or into the structure of the piece comprising at least a duct portion, within a through opening, being blocked rotatably between two complementary parts forming by assembly, by friction or by vibration welding said duct portion or said piece and being mounted in corresponding housing recesses obtained in the walls of the duct portions and/or in one or more corresponding separated or displaced bearings.

The invention will be better understood thanks to the following description of preferred embodi-

ments, given by way of non limiting examples and explained with reference to the attached schematic drawings, in which:

Figure 1 is a cross section view in lateral elevation of a duct portion comprising a regulation device according to the invention;

Figure 2 is a view following arrow A of the object shown in figure 1;

Figures 3 are perspective and partially sectioned views of an intake manifold before (Fig. 3A) and after (Fig. 3B) mounting a control shaft equipped with valves on a manifold or dispenser wall part containing structural parts of the intake pipes, according to a first embodiment of the invention;

Figure 4 is a detailed view on a different scale of a part of the object shown in figure 3B;

Figures 5 are partial sectioned and perspective views of a part of an intake manifold, on the outlet openings of the pipes, before mounting a shaft equipped with valves (Fig. 5A), after mounting said shaft (Fig. 5B) and after mounting the transmission means and the actuator (Fig. 5C), according to second embodiment of the invention;

Figure 6 is a detailed view following arrow B of the plug shown in figure 5 (the transmission means 14

having been removed);

Figure 7 is a schematic detailed view in lateral elevation of an intake pipe surrounded by a sealed case;

Figures 8 are schematic partial representations showing the assembly by vibration welding of two parts of a manifold in the area of an intake passage (Figures 8A, 8B and 8C: front perspective views), and its sealing by assembling a third part onto the outer surface of said passage (Figure 8D: view in lateral elevation), and

Figure 9 is a sectional view in lateral elevation of the solution shown in Figure 8D adapted to the intake passage 15' of the manifold shown in Figures 5, according to another embodiment of the invention.

The figures of the attached drawings show a device for regulating the flow of a fluid, in particular a gas, in at least a duct portion 1, an intake passage, an opening or similar (for instance a portion of a circulation circuit of any fluid) by means of a valve 3 or of a similar revolving obstruction element, supported by a control shaft 4.

According to the invention each assembly valve 3/control shaft 4 is integrated into the structure of

the duct portion 2 concerned or into the structure of the piece 1 comprising at least a duct portion 2, within a through opening, being rotatably supported between two complementary parts 2', 2'' or 1'', 1''' forming by assembly said duct portion 2 or said piece 1 and being mounted in corresponding housing recesses 5, 5' obtained in the walls of the duct portions 2 and/or in one or more corresponding separated or attached bearings 6 which are present on at least one of the parts 1'', 1''' forming piece 1.

The invention can be applied to a single duct portion 2 or to a single through opening as well as to a plurality of duct portions 2 or openings connected or not one to the other and arranged in any way one with respect to the other.

Therefore, according to a preferred embodiment of the invention, the regulation device can comprise an assembly valves 3/shaft 4 for a plurality of duct portions 2 or through openings of piece 1, each comprising a valve 3, all these valves being mounted or formed onto a single control shaft 4.

The expression "duct portion" should be understood in the present invention as any passage, circular or not, which can be obstructed by a moving element such as a valve. If necessary, said passage can

be reduced to a simple through opening, the axial or longitudinal size of the duct portion 2 being in this case strongly reduced, i.e. absent.

The valves 3 can be placed in a middle part of the ducts 2 or on the outlet openings of said ducts.

According to an embodiment, the control shaft 4 is "sandwiched" between parts 2', 2" constituting said at least one duct portion 2 or said piece 1, in the assembly and connection area of said parts 2', 2" or 1", 1"' (see Figures 1, 2 and 7).

Moreover, the assembly or connection lines 2"' deriving from the association between the assembly or connection surfaces of the two structural parts 2' and 3, can be located on a plane perpendicular to the axis of the duct portion 2 concerned, but also extend in other directions so as to simplify the assembly of the parts 2' and 2".

The assembly and connection surfaces should only be defined so as to end into at least one of the housing recesses 5, 5' and to cut the duct portion 2 concerned so as to enable the installation of the assembly control shaft 4/valve(s) 3 in at least one of the structural parts 2' and 2" or between them.

According to another embodiment of the invention, the control shaft 4 is placed on one of the

ends of the duct 2 and is fixed to wall portions (connecting for instance two adjacent ducts) in points shifted with respect to the duct wall.

The supporting and guiding functions of the control shaft 4 supporting the valve or valves 3 for its positioning and rotation can be achieved by means of different technical solutions which are described by way of non limiting examples in the following.

So, according to a first embodiment of the invention shown in particular in Figures 1, 2, 3 and 4, the support of control shaft 4 and its rotation can be guaranteed, partly at least, by at least a bearing 6 outside the wall or walls of the duct portion(s) 2 or of the piece 1 concerned, if necessary obtained by assembling two complementary parts, each of them being present on one of parts 1" and 1"' or pre-formed only on one of the two aforesaid parts.

The control shaft 4 can advantageously be mounted rotatably on one or more bearings 6 displaced with respect to the walls of the duct(s) 2 and formed on one 1" of the two parts 1", 1"' of piece 1, said shaft 4 being fixed and positioned by blocking it elastically on said bearings 6, 12 and said shaft 4 being blocked between said parts 1", 1"' without any contact with the other one 1"' of said two parts 1",

1'' either with the shaft 4 or the valves 3, or with the bearings 6.

Said bearings 6 can consist for instance of a generally U-shaped structure with one or two deformable or resilient wings or tangs 6' forming together or with an additional element said bearings 6 provided with a tapered opening holding elastically the shaft 4 after its introduction by displacing said wings equipped with opposite holding nibs 6'' (see in particular figures 3, 4 and 5).

In this embodiment of the invention, which can be applied in particular when the assembly shaft 4/valve(s) is placed on the outlet opening of the duct or ducts 2, none of the supporting or guiding bearings is located on the wall of the duct(s) 2 (see in particular figures 3 and 5).

According to a second embodiment shown in figures 1 and 2 of the attached drawings, at least one of the supporting and rotation guiding bearings 7 of the control shaft 4 can be obtained by cooperation of the opposite housing recesses 5, 5' located in the connecting areas of the walls of the two parts 2', 2'' or 1'', 1''' forming the duct portion(s) 2 or piece 1, said supporting or guiding bearings 7 being possibly sealed with or without the interposition of an at-

tached sealing element 8.

In order to simplify the rotation of the shaft 4 and to position it in the two aforesaid embodiments, said control shaft 4 can comprise one or more cylinder-shaped protuberances 9 or ring-shaped (disk-shaped) protuberances 9', obtained as one piece with said shaft 4 or attached onto the latter by over-forming or mounting, whose function is to cooperate with the supporting or guiding bearings 6, 7 or with translation blocking stops 10 of said control shaft 4.

The protuberances 9, 9' can advantageously be made of a wear-resisting material and/or of a material having a low coefficient of friction with the material constituting the supporting and guiding bearings 6 and 7, said ring-shaped protuberances 9 having the shape of sleeves possibly having disk-shaped stops 9'' on their opposite longitudinal ends so as to form translation blocking sites of shaft 4 after its mounting.

According to a third embodiment of the invention shown in figures 3 and 4 of the attached drawings, the control shaft 4 can also comprise one or more rotation guiding bearings 11 which are pre-mounted, blocked and clamped in supporting bearings 12 ob-

tained during the assembly of the two parts 2' and 2'' or 1'' and 1''' constituting the duct portion(s) 2 or piece 1.

The pre-mounted rotation guiding bearings 11, for instance in the form of roll or roller bearings, can possibly be completely inserted into the supporting bearings 12 so as to protect them and block their movement, which makes stops 10 useless.

It is obvious for people skilled in the art that the supporting and guiding function of the control shaft 4 can be achieved both using only one of the solutions described above or combining them together.

The assembly control shaft 4/valve(s) 3 can be obtained both by fixing (for instance by welding, screwing, clipping, bending or other methods) metal valves onto an shaft (made or not of metal), and by over-forming the valves onto a metal or plastic shaft (the guiding protuberances 9 or the bearings 11 being installed on the shaft before or after the over-forming operation), or also by forming as one piece an assembly shaft/valves in plastic.

The assembly between parts 2' and 2'' constituting duct portion 2 and/or between parts 1'' and 1''' constituting piece 1 can also be achieved with different methods, such as for instance mechanical con-

nection, gluing, welding or others, according to the material constituting said parts 2' and 2" or 1" and 1"'. .

It should also be pointed out that the control shaft 4 can be placed centrally with respect to the valve(s) 3 or, if necessary, shifted, so as not to disturb the flow when said valves 3 are open or in a position of maximum passage (see on this subject French patent application no. 99 02531 issued to the Applicant).

However, according to a preferred embodiment of the invention, the two parts 2' and 2" or 1" and 1"' constituting duct portion 2 and/or piece 1 are made of thermoplastic material and assembled by vibration welding, the connection planes being configured and arranged so as to enable, if necessary, the installation of the assembly control shaft 4/valve(s) 3 on or within one at least of said two parts or between them.

The holes for the shaft 4 can be sealed by forming a gasket during assembly, by means of a separate sealing element attached before or after assembly, or by attaching an additional part or piece 17 by vibration welding onto the outer surface of the hole(s) concerned, said additional part containing, if neces-

sary, an axially sealed supporting and guiding bearing 6, 12.

The achievement of this third solution is shown in particular in figures 8 and 9 of the attached drawings.

As shown by said figures, the hole 15' is formed first of all during assembly of pieces 1" and 1"' by overlapping on the opposite portions of their weld beads 19' and 19" (figures 8A and 8B), so as to obtain a transversally sealed passage 15' whose outer outlet opening is surrounded (on the outer surface of piece 1) by two semicircular weld bead portions (figure 8C) forming together a circular bead surrounding said opening.

The coincident circular bead 19"' of a sealed piece 17 is then applied onto the two semicircular beads 19' and 19", said elements being then assembled by vibration welding (figure 8D: view in lateral elevation), so as to obtain a sealed assembly of pieces 1 and 17.

Another object of the present invention is also an intake manifold or splitter 1 comprising at least one, and preferably a plurality of intake pipes 2 in the form of duct portions connecting the chamber of the manifold or dispenser with the heads, and ob-

tained by assembling at least two complementary parts 1", 1"' in thermoplastic material by vibration welding (see figures 3 to 5 and 7 to 9).

Said intake manifold or splitter 1 is characterized in that at least some of the pipes 2 or through openings of the latter, and preferably all of them, comprise a regulation device such as the one described above, integrated into the structure of said manifold or dispenser 1 and forming an assembly for flow regulation comprising a plurality of valves 3 mounted or formed onto a unique control shaft 4 passing through said intake pipes 2 or through openings and provided on one of its ends with an interconnecting element 13, in particular at least a rotation coupling element, with a transmission means 14 connected with an actuator 14' or directly equipped with an actuator.

Said actuator 14' can be of pneumatic, electric, mechanical or other type.

According to a preferred embodiment of the invention, the control shaft 4 provided with valves 3 extends transversally near one of the ends of the intake pipes 2, i.e. as far as its connection area with wall 1' of the chamber of manifold 1 or as far as its connection area with the fixing plate on the heads,

the supporting bearings 12 and, if necessary, the guiding bearings 6, 7, as well as the translation blocking stops 10 of the control shaft 4 being at least partially, and preferably completely, formed onto said wall 1' of the manifold chamber or onto said fixing plate.

Said stops 10 can consist both of protuberances of wall 1' (figures 3) and of recesses of the latter (figures 5).

In particular, said assembly control shaft 4/valves 3 can be placed on the interface intake pipe 2/chamber of manifold 1 or on the interface intake pipe 2/heads. In particular in the first case, the assembly can be "sandwiched" between two parts 1" and 1"' forming the chamber of said manifold or splitter and having an assembly or connection plane or line going across said interface area pipe/manifold on the outlet openings of said pipes within the chamber of said manifold (figures 3 to 5).

According to another embodiment of the invention, shown in particular in figures 3 to 5, 7 and 9 of the attached drawings, the control shaft 4 freely goes (without contact) through the walls of the intake pipes 2 concerned or extends through the openings of said pipes 2 getting into the chamber of

manifold 1, the assembly of the structural parts 1", 1"' of manifold 1 creating a sealed case 15 around the connection areas of the assembly of said intake pipes 2 together with wall 1' of manifold 1 or where said pipes 2 get into the chamber of manifold 1, the piece formed by the assembly control shaft 4/valves 3 being mounted by introduction into bearings 6, 12 pre-formed onto the wall 1' of one 1" of the pieces 1", 1"' forming manifold 1, on cylinder-shaped protuberances 9 or on bearing portions 11 formed or attached onto shaft 4, the other one 1"' of said pieces 1", 1"' possibly preventing the coming out of shaft 4 from said bearings 6, 12 after assembling the two pieces 1" and 1"'.

According to first embodiment of the invention, shown in particular in figures 3, 4 and 5 of the attached drawings, said sealed case 15 is completed on opening 15 for the portion of control shaft 4 getting out and supporting the interconnecting element 13, or for the re-entrant handling bar 14" of the transmission means 14, by means of a ring-shaped axial plug 16, shrink-fitted or tight-fitted or welded onto said opening 15' (said plug possibly supporting sealing elements for the passage of shaft 4 or being itself a sealing element while enabling the rotation of the

handling bar 14" and/or of means 14).

According to another embodiment, shown in particular in figure 9 of the attached drawings, the sealed case 15 formed by assembling the two parts 1" and 1"' of manifold 1 is closed on the opening 15' for the portion of control shaft 4 getting out and supporting the interconnecting element 13 or for the re-entrant handling bar 14" of the transmission means 14, by interconnection, by vibration welding, on the opening or on the outer surface of said passage 15', by means of a third hollow part 17 closing at least a component of the transmission means 14 and/or at least an axially sealed bearing 6, 12, said third part 17 being interconnected after forming piece 1.

Preferably, as shown in figures 5A, 5B and 5C of the attached drawings, the assembly shaft 4/valves 3 fully extends within the sealed case 15, the shaft 4 not going across the welding assembly areas or lines, the two valves 3 at the opposite ends of shaft 4 being mounted protrudingly and valve 3 positioned near the opening 15' being provided with an axial blind channel 18, for instance with rectangular section, housing by coupling the end of handling bar 14" and forming the interconnecting element 13.

As shown in figure 3A of the attached drawings,

the interconnecting element 13 can alternatively be in the form of a square-section extension of control shaft 4, connected with a female piece having a housing sleeve with complementary shape (for instance by clipping, by gluing, by tight fitting and/or shrink fitting or similar) being part of the transmission means 14 connected with an actuator.

The driving gear of control shaft 4 can enable the shifting of valves 3 between an opening and a closing position (complete or not), the extreme positions being defined by one or more mechanical stops connected with the control shaft and preferably located near the actuator 14'. The shifting between the opening and closing positions can be carried out both with a full/empty pattern and proportionally.

So, the connection between control shaft 4 and transmission means 14 can be carried out both outside and preferably inside the sealed case formed during the assembly of the two structural parts 1" and 1"' of manifold 1, the aforesaid female or male piece thus sealingly extending through a corresponding through opening 15'.

Moreover, a further object of the present invention is a method to produce an intake manifold or splitter 1 such as the one described above, starting

from at least two parts 1", 1"' made of thermoplastic material.

Said method essentially consists in providing a first part 1" of an intake manifold 1, in installing on or within said first part 1" and within recesses 5, 5' and/or portions of suitable supporting or guiding bearings 6, 12, a control shaft comprising a plurality of valves 3 arranged each within a through opening or a part passage 2' of corresponding intake pipe 2, in providing at least a second part 1"' of the intake manifold (1) comprising, if necessary, the complementary parts 2" of intake pipes 2 and in arranging it or them in assembling position with the first part 1" blocking or "sandwiching" the control shaft 4 with valves 3, and finally in assembling by vibration welding said at least two parts 1", 1"' of intake manifold 1.

The second part 1"' can both participate directly in blocking the assembly shaft 4/valves 3 being in direct contact with said assembly ("sandwiching" and fitting shaft 4 between the two parts 1" and 1"', possibly on the assembly line between the two parts 2' and 2" of duct portions 2), and be only a covering portion or a cover for the first part 1", the latter assuring, if necessary,

only the supporting and rotation guiding functions of the assembly shaft 4/valves 3.

So, advantageously, as shown in figures 3 and 5 of the attached drawing, the mounting of the assembly shaft 4/valves 3 is achieved by fitting onto said first part 1", and the assembly of the two parts 1" and 1"' results in a sealed case 15 around said assembly except for a drawing opening 15', the latter being sealed while coupling the transmission means 14 with the control shaft 4.

The description above shows how the aim underlying the invention consists first of all in mounting the assembly control shaft 4/valve(s) 3 onto a part 1", 2' or between two parts 1" and 1"', 2' and 2" (said assembly possibly being kept in place by bearing portions 5, 5', 6 or 11), then in assembling the two parts 1" and 1"', 2' and 2" constituting the duct portion 2, the manifold or splitter 1 or any other element or structure comprising a regulation device according to the invention.

The invention allows to achieve a technical solution minimizing the number of operations which are necessary for installing and mounting the regulation device (without interfering with the fabrication method existing and without making it longer), said

technical solution having small overall dimensions and enabling a complete integration of said regulation device (protection against collisions), though assuring a reliable sealing.

The invention is obviously not limited to the embodiments described and shown in the attached drawings. Changes are still possible, in particular as far as the constitution of the various elements is concerned or by replacing with technical equivalents, though without leaving the protection field of the invention.

CLAIMS

1. Device for regulating the flow of a fluid, in particular a gas, in at least a duct portion, an intake passage or similar by means of a valve or of a similar rotating obstruction element, supported by a control shaft, characterized in that each assembly valve (3)/control shaft (4) is integrated into the structure of the duct portion (2) concerned or into the structure of piece (1) comprising at least a duct portion (2), on a through opening, being rotatably supported between two complementary parts (2', 2" or 1", 1'') forming by assembly, by friction or vibration welding said duct portion (2) or said piece (1) and being mounted in corresponding housing recesses

(5, 5') obtained in the walls of the duct portions (2) and/or in one or more corresponding separated or displaced bearings (6) which are present on at least one of parts (1'', 1''') forming piece (1).

2. Device according to claim 1, characterized in that the support of the control shaft (4) and its rotation guiding are assured, at least partly, by at least a bearing (6) placed outside the wall or wall of duct portion(s) (2) or of piece (1) concerned, formed if necessary by assembling the two complementary parts.

3. Device according to claim 2, characterized in that the control shaft (4) is mounted rotatably on one or more bearings (6) displaced with respect to the walls of the duct(s) (2) and formed on one (1'') of the two parts (1'', 1''') of piece (1), said shaft (4) being fixed and positioned by blocking it elastically onto said bearings (6, 12) and said shaft (4) being blocked between said parts (1'', 1''') without any contact with the other one (1''') of said two parts (1'', 1''').

4. Device according to any of the claims 1 and 2, characterized in that the control shaft (4) is "sandwiched" between the parts (2', 2'') constituting said at least one duct portion (2) or said piece (1),

5. Device according to any of the claims 1, 2 and 4, characterized in that at least one of the supporting and rotation guiding bearings (7) of the control shaft (4) is obtained by cooperation of the opposite housing recesses (5, 5') in the connection areas of the walls of the two parts (2', 2" or 1", 1'') forming the duct portion(s) (2) or the piece (1), said supporting and guiding bearing(s) (7) being possibly sealed with or without interposition of an attached sealing element (8).

6. Device according to any of the claims 2 to 5, characterized in that the control shaft (4) comprises one or more cylinder-shaped protuberances (9) or ring-shaped protuberances (9') obtained as one piece with said shaft (4) or attached onto the latter by over-welding or mounting and cooperating with the supporting and guiding bearings (6, 7) or with translation blocking stops (10) of said control shaft (4).

7. Device according to any of the claims 1 to 6, characterized in that the control shaft (4) comprises one or more pre-mounted rotation guiding bearings (11), blocked within supporting bearings (12) formed during the assembly of the two parts (2' and

2" or 1" and 1"'') constituting the duct portion(s) (2) or the piece (1).

8. Device according to any of the claims 1 to 7, characterized in that the two parts (2' and 2" or 1" and 1"'') constituting the duct portion (2) and/or the piece (1) are made of thermoplastic material, the opening for the shaft (4) being sealed by forming a gasket during assembly by vibration welding, by means of a separate sealing element attached before or after assembly or by attaching an additional part (17) by vibration welding onto the outer surface of the passage concerned, said additional part being able, if necessary, to house an axially sealed supporting and guiding bearing (6, 12).

9. Device according to any of the claims 1 to 8, characterized in that it comprises an assembly valves (3)/shaft (4) extending to several duct portions (2) or through openings of piece (1), each comprising a valve (3), all said valves (3) being mounted or formed onto a unique control shaft (4).

10. Intake manifold comprising at least one, and preferably a plurality of intake pipes in the form of duct portions connecting the chamber of the manifold with the heads, and obtained by assembling at least two complementary parts made of thermoplas-

tic material by vibration welding, characterized in that at least some of the pipes (2) or through openings of the latter, and preferably all of them, comprise a regulation device according to any of the claims 1 to 9, forming an assembly for flow regulation comprising a plurality of valves (3) mounted or formed onto a unique control shaft (4) passing through said intake pipes (2) or through openings and provided on one of its ends with an interconnecting element (13), in particular at least a rotation coupling element, with a transmission means (14) connected with an actuator (14') or directly equipped with an actuator.

11. Intake manifold according to claim 10, characterized in that the control shaft (4) provided with valves (3) extends transversally near one of the ends of the intake pipes (2), i.e. as far as its connection area with wall (1') of the chamber of manifold (1) or as far as its connection area with the fixing plate on the heads, the supporting bearings (12) and, if necessary, the guiding bearings (6, 7), as well as the translation blocking stops (10) of the control shaft (4) being at least partially, and preferably completely, formed onto said wall (1') of the chamber of manifold (1) or onto said fixing plate.

12. Intake manifold according to claim 11, characterized in that the control shaft (4) freely goes through the walls of the intake pipes (2) concerned without contact or extends through the openings of said pipes (2) getting into the chamber of manifold (1), the assembly of the structural parts (1'', 1''') of manifold (1) creating a sealed case (15) around the connection areas of the assembly of said intake pipes (2) together with wall (1') of manifold (1) or where said pipes (2) get into the chamber of manifold (1), the piece formed by the assembly control shaft (4)/valves (3) being mounted by introduction into bearings (6, 12) pre-formed onto wall (1') of one (1'') of the pieces (1'', 1''') forming manifold (1), on cylinder-shaped protuberances 9 or on bearing portions (11) formed or attached onto the shaft (4), the other one (1''') of said pieces (1'', 1''') possibly preventing the coming out of the shaft (4) from said bearings (6, 12) after assembling the two pieces (1'' and 1''').

13. Intake manifold according to claim 12, characterized in that said sealed case (15) is completed on opening (15') for the portion of the control shaft (4) getting out and supporting the interconnecting element (13) or for the re-entrant han-

dling bar (14") of the transmission means (14), by means of a ring-shaped shaft plug (16) shrink-fitted or tight-fitted or welded onto said passage (15').

14. Intake manifold according to claim 12, characterized in that the sealed case (15) formed by assembling the two parts (1" and 1"') of manifold (1) is closed on the opening (15') by the portion of the control shaft (4) getting out and supporting the interconnecting element (13) or by the re-entrant handling bar (14") of the transmission means (14), by interconnection, by vibration welding, on the opening or on the outer surface of said passage (15'), by means of a third hollow part (17) closing at least a component of the transmission means (14) and/or at least an axially sealed bearing (6, 12).

15. Intake manifold according to any of the claims 13 and 14, characterized in that the assembly shaft (4)/valves (3) fully extends within the sealed case (15), said shaft (4) not going across the welding assembly areas or lines, the two valves (3) at the opposite ends of the shaft (4) being mounted protrudingly and the valve (3) positioned near passage (15)' being provided with an axial blind channel (18), for instance with rectangular section, housing the end of handling bar (14") inserted within.

16. Method to produce an intake manifold according to any of the claims 10 to 15, starting from at least two parts made of thermoplastic material, characterized in that it consists in providing a first part (1'') of an intake manifold (1), in installing on or within said first part and within recesses (5, 5') and/or portions of suitable supporting or guiding bearings (6, 12), a control shaft (4) comprising a plurality of valves (3) arranged each within a through opening or a part passage (2') of corresponding intake pipe (2), in providing at least a second part (1''') of the intake manifold (1) comprising, if necessary, the complementary parts (2'') of intake pipes (2) and in arranging it or them in assembling position with the first part (1'') blocking or "sandwiching" the control shaft (4) with valves (3), and finally in assembling by vibration welding said at least two parts (1'', 1''') of intake manifold (1).

17. Method according to claim 16, characterized in that the mounting of the assembly shaft (4)/valves (3) is carried out by fitting onto said first part (1'') and in that the assembly of the two parts (1'' and 1''') results in a sealed case (15) around said assembly except for a drawing passage (15'), the lat-

ter being sealed when coupling the transmission means (14) with the control shaft (4).

(12) DEMANDE INTERNATIONALE PUBLIÉE EN VERTU DU TRAITE DE COOPÉRATION
EN MATIÈRE DE BREVETS (PCT)(19) Organisation Mondiale de la Propriété
Intellectuelle
Bureau international(43) Date de la publication internationale
8 mars 2001 (08.03.2001)

PCT


(10) Numéro de publication internationale
WO 01/16473 A1

- (51) Classification internationale des brevets⁷: F02D 9/10, F02M 35/10
- (21) Numéro de la demande internationale: PCT/FR00/02413
- (22) Date de dépôt international: 31 août 2000 (31.08.2000)
- (25) Langue de dépôt: français
- (26) Langue de publication: français
- (30) Données relatives à la priorité: 99/10999 31 août 1999 (31.08.1999) FR
- (71) Déposant (pour tous les États désignés sauf US): MARK IV SYSTEMES MOTEURS (SOCIÉTÉ ANONYME) [FR/FR]; 4, place des Saisons, F-92400 Courbevoie (FR).
- (72) Inventeurs; et
- (75) Inventeurs/Déposants (pour US seulement): MOREAU, Fabien [FR/FR]; 28, route de Colmar, F-68370 Orbey (FR). KOMURIAN, Richard [FR/FR]; 1, rue des Bénédictins, F-68230 Turckheim (FR).
- (74) Mandataire: CABINET NUSS; 10, rue Jacques Kablé, F-67080 Strasbourg Cedex (FR).
- (81) États désignés (national): JP, US.
- (84) États désignés (régional): brevet européen (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).
- Publiée: — Avec rapport de recherche internationale.

[Suite sur la page suivante]

(54) Title: DEVICE FOR REGULATING FLOW IN A DUCT PORTION OR AN INTAKE PASSAGE AND MANIFOLD COMPRISING SAME

(54) Titre: DISPOSITIF DE REGULATION DE L'ÉCOULEMENT DANS UNE PORTION DE CONDUIT OU UN PASSAGE ET COLLECTEUR COMPRENANT UN TEL DISPOSITIF



(57) Abstract: The invention concerns a device for regulating flow in a duct portion or an intake passage and a manifold comprising such a device. The device is characterised in that each valve (3)/control pin (4) assembly is incorporated in the structure of said duct portion (2) or in the structure of the part (1) comprising at least a duct portion (2), at the opening of a through passage, being enclosed, with the possibility of rotating between two matching parts (2', 2'' or 1', 1'') forming by being assembled said duct portion (2) or said part (1) and being mounted in corresponding housing recesses (5, 5') provided in the walls of duct portions (2) and/or in one or several separate corresponding bearing(s) (6).

[Suite sur la page suivante]



WO 01/16473 A1

Fig-1








Fig-2










Fig-5B

Fig-5




Fig-5C

Fig-5




Fig-6




Fig-7




Fig. 8B




Fig. 8A






Fig. 8

Fig. 1

Fig. 2

Fig. 3





COMBINED DECLARATION AND POWER OF ATTORNEY

As below named inventor(s), I/we declare that:

My/our residence, post office address(es) and citizenship(s) is/are as stated below next to my/our name(s); that I/we believe I/we am/are the original, first and sole/joint inventor(s) of the subject matter which is claimed and for which a patent is sought on the invention or design entitled:

Device for regulating flow in a duct portion or an intake passage and manifold comprising same

the specification of which:

___ is attached hereto; or

X was filed on February 26, 2002 as Application Serial No. 10/069,507 and was amended on

I/we hereby state that I/we have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above; and that I/we acknowledge the duty to disclose to the U.S. Patent and Trademark Office all information known to me/us to be material to patentability as defined in Title 37, Code of Federal Regulations, §1.56.

I/we hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate or any PCT international application(s) designating at least one country other than the United States of America listed below and have also identified below any foreign application(s) for patent or inventor's certificate or any PCT international application(s) designating at least one country other than the United States of America filed by me/us on the same subject matter having a filing date before that of the application(s) on which priority is claimed:

<u>COUNTRY</u>	<u>NUMBER</u>	<u>DATE FILED</u>	<u>PRIORITY CLAIMED</u>
France	9910999	August 31, 1999	YES <u>X</u> NO <u> </u> YES NO

I/we hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) or PCT application(s) designating the United States of America that is/are listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application(s) in the manner provided by the first paragraph of Title 35, United States Code, §112, I/we acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56(a) which occurred between the filing date of the prior application(s) and the national or PCT international filing date of this application:

APPLICATION SERIAL NUMBER

PCT/FR00/02413

DATE FILED

August 31, 2000

STATUS

I/we hereby appoint Robert J. Schneider (Reg. No. 27,383), John R. Crossan (Reg. No. 27,433), and Jane S. Berman (Reg. No. 43,494), all of the Bar of the State of Illinois, all of Chapman and Cutler, and using the address 111 West Monroe Street, Chicago, IL 60603, my/our attorney with full power of substitution and revocation, to prosecute this application and to transact all business in the United States Patent and Trademark Office connected therewith, and to file and prosecute any international patent applications filed thereon before any international authorities under the Patent Cooperation Treaty and I/we hereby authorize him to act and rely on instructions from and communicate directly with the person/assignee/attorney/firm/organization who/which first sends/sent this case to him and by whom/which I/we hereby declare that I/we have consented after full disclosure to be represented unless/until I/we instruct him in writing to the contrary.

It is requested that all correspondence be directed to:

ROBERT J. SCHNEIDER
CHAPMAN AND CUTLER
111 WEST MONROE STREET
CHICAGO, ILLINOIS 60603

